

Product Info: Gooseneck Nozzle

The gooseneck curve with nozzle is developed for small openings.
Depending on the bent curve fits it through a thread.

G 2	56,6 mm
G 2½	72,2 mm
G 3	84,9 mm



Opening (core diameter) from
tube threads according to DIN ISO 228, part 1

Gooseneck curve **with fixed welded** nozzle (Art.-No.: 2.05):

nozzle opening	according to EN 13284	leg length (L)	opening G 2	opening G 2½	opening G 3
4-6 mm	No	51 mm	☺	☺	☺
8 mm	Yes	51 mm	☺	☺	☺
10-14 mm	No	51 mm	☺	☺	☺
15 mm	No	57 mm	☹	☺	☺
16 mm	No	58 mm	☹	☺	☺
18 mm	No	65 mm	☹	☺	☺
19 mm	No	66 mm	☹	☺	☺



Standard gooseneck curve **with exchangeable** nozzle:
(Art.-No.: 2.07-K, S: 42 mm)

nozzle opening	according to EN 13284	leg length (L)	opening G 2	opening G 2½	opening G 3
4-14 mm	Yes	77 mm	☹	☹	☺
15 mm	Yes	81 mm	☹	☹	☺
16 mm	Yes	84 mm	☹	☹	☹



Short gooseneck curve **with exchangeable** nozzle:
(Art.-No.: 2.07-KV, S: 30 mm)

nozzle opening	according to EN 13284	leg length (L)	opening G 2	opening G 2½	opening G 3
4-6 mm	No	65 mm	☹	☺	☺
8-10 mm	Yes	65 mm	☹	☺	☺
12-14 mm	No	65 mm	☹	☺	☺
15 mm	No	69 mm	☹	☺	☺
16 mm	No	72 mm	☹	☹	☺
18 mm	No	77 mm	☹	☹	☺
19 mm	No	83 mm	☹	☹	☹
20 mm	No	85 mm	☹	☹	☹

