

Product info 47: Holder for suction tubes

Holders

for fixing the suction tube at the measuring point. The holder needs at least the length of half a sleeve / socket (approx. 30 mm).



Gas-tight holders

made of stainless steel for suction tubes with external Ø 25, 33, 50 or 60 mm. The gas-tight closure is achieved by a packing cord which is pressed against a flange on the suction tube by means of screwing. For shifting the suction tube must loosen the flange,



with external thread G 2:	Art.-No.: 47.11
with external thread G 2½:	Art.-No.: 47.12
with external thread G 3:	Art.-No.: 47.13

Length: ca. 90 mm



Quick fastener holder

material: stainless steel pipe with two aluminium half-pans on the inside. The lower half-pan is firmly screwed on while the upper pan is moved by a toggle. The holder is not gas-tight. Shifting the suction tube works fast and easily through the toggle. The suction tube is not damaged by the half-pans even under strong loading. The half-pans are adapted to the required external Ø of the suction tube.

For suction tubes with external Ø: 25, 33, 50 or 60 mm.
Length: ca. 170 mm



Small holder (for suction tubes with Ø: 25-33 mm)

with External thread G 2	Art.-No.: 47.31
with External thread G 2½	Art.-No.: 47.32
with External thread G 3	Art.-No.: 47.33

Big holder (for suction tubes with Ø: 33-60 mm)

with External thread G 2	Art.-No.: 47.21
with External thread G 2½	Art.-No.: 47.22
with External thread G 3	Art.-No.: 47.23

Sleeve reduction



The holder can be adapted to the different coupling sleeves / sockets at the measuring points through sleeve reductions (bushing (M/F)). The sleeve reduction is composed of stainless steel and an internal thread.

Reduction of G 3 to G 2:	Art.-No.: 47.41
Reduction of G 2½ to G 2:	Art.-No.: 47.42